

Slimwood Overlay

Contributed by World of Timber
Last Updated Tuesday, 09 October 2007

Slimwood by Boral

Precision-milled to 13mm thick, thinner than the traditional tongue and groove strip floors. Slimwood goes down directly over a structural surface such as concrete or plywood, it is well supported and there is no disadvantage in the thinner product. When compared to traditional 19mm tongue and groove strip flooring, Slimwood still offers the same depth of wear (the depth of the board that can be sanded and refinished) even the overall plank is 6mm thinner.

Easy Installation

Slimwood solid timber flooring is designed to be glued down using Bostik Ultraset polyurethane adhesive. As any solid timber product will be affected by changes in the moisture content of the air, it is recommended that Slimwood is left to acclimatise to its new environment for an appropriate time. In areas where there is a concern with moisture, Bostik Moisture Seal should be used in conjunction with Bostik Ultraset. Your new floor should then be professionally installed and only takes a short time to install, sand and finish.

Versatility

Slimwood can be used in the following flooring applications:

- over a concrete slab
- over old timber floors - as long as they are flat
- over particleboard or plywood subflooring

Environmentally friendly

Timber is one of the world's few truly renewable natural resources. The native hardwood that you buy from World of Timber is sourced from a forest that is sustainably managed through a rigorous framework of both Commonwealth and State laws and regulations.

Sizes and lengths available:

- 85mm wide x 12mm thick
- Random lengths 0.6m to 2.4m

- Available in 2m² easy-to-handle bundles

Grades available:

- Select - minimal natural variations
- Standard - beautiful variations in colour and grain as well as natural features such as gum veins and insect trails